

Description

Linnet IP65 LED Moisture proof luminaire is available for surface or suspended installations. The range offers single or double row of LEDs (see options below)

Linnet has a sealed polycarbonate enclosure with a specially made opal diffuser and stainless steel clips, ideal for installations with low ambient temperatures ideal for undercover car parks as well as warehouse, back of house and food areas, to name a few.

Dimmable control option along with other options as below. It is an ideal replacement for fluorescent luminaires and can offer great savings and a fast pay back. (Please email for more details if survey required)



Dimensions

Single: 75mm (W) x 75mm (H)

Double: 110mm (W) x 75mm (H)

Options

Description

DALI Dimmable
Emer 3 hour integral
EMPRO Emergency

Add to part code

/DALI
/EM3
/EMPRO

Standard options

1200mm single (1650lm)
1200mm double (3860lm)
1500mm single (2330lm)
1500mm double (4550lm)

Order code

3846122
3846146
3846127
3846153

Information

Light Source:	LED
Wattage:	Various see options
Housing	Polycarbonate
Diffuser	Opal
IP rating :	IP65: Ta25
Insulation Class	Class 1 - EN60598
Control:	DALI driver available
Lifetime:	50,000 hours
Maximum Weight:	4kg
Warranty:	3 years