

Description

Grebe LED linear fittings are designed to give an even light distribution with its smart light guide cover, smooth IP44 dust free and easy to clean. Grebe has a high lumen output with up to 130lm/tcW, with an integral Tridonic driver. Designed with education and healthcare at the forefront, Grebe is perfect for Colleges, University's, Hospital's but also ideal for numerous other applications. Grebe can offer great savings and a fast pay back. Please contact us for more details if survey required.



Options

Description

White finish
DALI Dimmable
1-10v Dimmable
Sensor
Colour Temperature (Standard 4000K)
for 3000K

Add to part code

Standard
/DALI
Standard
/S
/3K

Information

Light Source: LED
Wattage: Various see options
Control: DALI driver available
CRI: >80
Power Factor: >90
Ambient temp: -40°C to + 25°C
Lifetime: 72,000+ hours
Warranty: 5 years

Standard options

Dimensions

Order code

3000K 20W 2355lm	1200mm, 207mm, 80mm (nom)	5834120-3K
3000K 33W 3677lm	1200mm, 207mm, 80mm (nom)	5834133-3K
3000K 41W 4550lm	1200mm, 207mm, 80mm (nom)	5834141-3K
4000K 19W 2395lm	1200mm, 207mm, 80mm (nom)	5844119
4000K 32W 3803lm	1200mm, 207mm, 80mm (nom)	5844132
4000K 40W 4700lm	1200mm, 207mm, 80mm (nom)	5844140
3000K 33W 4301lm	1500mm, 207mm, 80mm (nom)	5834133-15-3K
3000K 43W 5257lm	1500mm, 207mm, 80mm (nom)	5834143-15-3K
3000K 55W 6425lm	1500mm, 207mm, 80mm (nom)	5834155-15-3K
4000K 33W 4307lm	1500mm, 207mm, 80mm (nom)	5844133-15
4000K 42W 5264lm	1500mm, 207mm, 80mm (nom)	5844142-15
4000K 54W 6600lm	1500mm, 207mm, 80mm (nom)	5844154-15