



## Description

Linnet/IK10 IP65 LED Moisture proof luminaire is available for surface or suspended installations. Linnet/IK10 is made from robust injection moulded polycarbonate body with micro prism, high impact diffuser. The Tridonic LEDs strips are covered with a micro prismatic diffuser for visual comfort and efficiency. High system efficacy to aid compliance with Building Regulations Part L and quick release flush mounted stainless steel fixing clips.

Linnet/IK10 are ideal for installations with low ambient temperatures ideal for undercover car parks as well as warehouse, back of house and food areas, to name a few.

Dimming, sensor and emergency are all an option along with other options as below. It is an ideal replacement for fluorescent luminaires and can offer great savings and a fast pay back. Please email for more details or if survey required

### Wall Bracket



## Options

### Description

DALI Dimmable  
Emer 3 hour integral  
Sensor on/off  
Stainless steel clips  
Wall bracket  
Sus kit 1.5m  
PIR Sensor

### Add to part code

/DALI  
/EM3  
/SO  
/SS  
/WB  
/SK1.5  
/PIR

### Standard options

3675lm 23W 4000K 1200mm  
4475lm 28.5W 4000K 1200mm  
5325lm 35.5W 4000K 1200mm  
6100lm 40.5W 4000K 1200mm

### Order code

3846123-1200-IK10  
3846128-1200-IK10  
3846135-1200-IK10  
3846140-1200-IK10

5300lm 33W 4000K 1500mm  
6625lm 41.5W 4000K 1500mm  
7950lm 50W 4000K 1500mm  
9250lm 59W 4000K 1500mm

3846133-IK10  
3846141-IK10  
3846150-IK10  
3846159-IK10

## Information

|                    |                     |
|--------------------|---------------------|
| Light Source:      | LED                 |
| Wattage:           | Various see options |
| Housing            | Polycarbonate       |
| Diffuser           | Micro Prismatic     |
| IP rating:         | IP65                |
| Impact protection: | IK10                |
| Power Factor:      | >0.9                |
| MacAdam:           | 3SDCM               |
| Colour rendering:  | Ra80                |
| Lifetime:          | 50,000 hours+       |
| Maximum Weight:    | 3kg & 4kg           |
| Ambient temp:      | -25°C to 30°C       |