

Recessed, Surface or suspended LED System


SWAN Suspended

Description

Swan is a range of LED system, designed for continuous lines of light not only functional but also giving interest to any application. Available in recessed, surface or suspended. Standard lengths are below but please request alternative lumen outputs. Corners, T sections, X sections are available with continuous light output. Also various dimming and emergency options.

Swan houses the most efficient latest generation LEDs with long life and energy efficiency. Extrusions can be up to 3mts in length and then joined on site for longer requirements. Surface and recessed options can be vertically or horizontally mounted. Choice of optics and lumen output. Infills available as required and can have PIRs etc housed within. Surface mounted version has a mounting plate which is fitted to the ceiling in first fix. Suspended versions have an adjustable 1.5mt suspension supplied as standard.

Please contact us for more information or specific requirements




For 80mm x 80mm
profile add -8080 to
part number as below


MPO - Microprism with
opal sheet



MP - Microprism



Standard - Opal



Options

Description

Add to part code

White
Opal diffuser
Indirect/Direct
Microprism optic
Microprism optic with opal sheet
DALI Dimmable
Colour Temperature 4000K
Colour Temperature 3000K
Suspension kit 1.5mts
Suspension kit 3mts (other lengths available)
CRI90
80mm x 80mm profile

Standard
Standard
/UD
/MP
/MPO
/DALI
Standard
/3K
Standard
/3
/CRI90
/8080

Information

Light Source: LED
Wattage: See options and enquire for specific wattages
Uplight Wattage: Various please enquire for specific requirements
Housing: Extruded Aluminium
Lengths: Various please enquire for specific
Optic: Various see options
IP rating : IP20
Control: DALI driver available

Standard Suspended options

592mm (nom) 4000K 13.5W 1551lm
872mm (nom) 4000K 19.6W 2328lm
1152mm (nom) 4000K 25W 3103lm
1482mm (nom) 4000K 31W 3878lm

Order code

23844313
23844320
23844325
23844331

Standard Suspended options

592mm (nom) 4000K 13.5W 1647lm
872mm (nom) 4000K 19.6W 2470lm
1152mm (nom) 4000K 25W 3293lm
1482mm (nom) 4000K 31W 4117lm

Order code

23844313-MPO
23844320-MPO
23844325-MPO
23844331-MPO

Please contact us for specific lumen output.

KB Lighting – Interior and exterior lighting solutions for business 01489 799174 info@kb-lighting.com kb-lighting.com

All details and specifications shown in this document are deemed correct at time of publication. The right to modify equipment, change specifications and instructions without notice, is reserved as part of the KB Lighting Limited policy of continuous development and improvement. We endeavour to keep all our customers informed of any alterations as and when they occur. E&O.E

