

IP65 LED Wall or Ceiling mounted Luminaire

SEDGE

Description

Sedge IP65 LED Wall mounted luminaire is corrosion and vandal resistant, giving exceptional light output. Made of die cast aluminium housing, fitted with stainless steel screws and silicon rubber gasket. Easy installation with 2 x 20mm cable entries on the side.

Suitable for wall or ceiling installations. Available in standard colours below or any RAL colour and either 3000K or 4000K. Various options including Dali Dimming, Sensors and/or Integral 3 hour Emergency.

Please contact us for more information



Options

Description

Black finish
Silver finish
Anthracite Grey
3000K
DALI Dimmable
1-10V
Microwave sensor
Photocell
Emer 3 hour integral
EMPRO Emergency
Without Eyelid

Add to part code

Standard
/SV
/AG
/3K
/DALI
/1-10V
/MS
/PC
/EM3
/EMPRO
/WO

Standard options

1509lm 3000K 23W
1573lm 4000K 23W

Order code

24833123
24843123

Information

Light Source:	LED
Wattage:	Various see options
Housing	Die Cast Aluminium
Diffuser	Polycarbonate Opal
Colour Rendering	CRI>80
Ambient Temperature	-25°C to 35°C
IP rating :	IP65
Insulation Class	Class 1 - EN60598
Control:	DALI driver available
Lifetime:	50,000 hours

Standard options

1896lm 3000K 23W
1992lm 4000K 23W

Order code

24833123-WO
24843123-WO