

Recessed LED Flat Panel

CASIN ECO

Description

Casin Eco is a slim LED panel fitting, comprising of edge lit LEDs giving constant, even, light distribution across the surface of the luminaire.

The standard Casin Eco has a white housing with a polycarbonate (TPb) or PMMA diffuser and is designed to sit within an exposed T ceiling. Offering versatility with suspension kits and surface mounted housing it offers solutions for different areas and ceiling restrictions.

With UGR<19 according to BS EN 12464 and dimmable control option along with other options as below it is an ideal replacement for fluorescent luminaires and can offer great savings and a fast pay back. (Please email for more details if survey required)



Options		Information	
Description	Add to part code	Light Source:	LED
White finish	Standard	Wattage:	See options
Suspension kit	/SK	Housing:	White
Surface mounted housing white	/SUR/WH	Diffuser:	PMMA
Plasterboard mounting	/PL	Diffuser option:	Polycarbonate (TPb)
4000K	Standard	UGR:	<19 according to BS EN 12464
3000K	/3K	CRI:	>80
DALI Dimmable	/DALI	Power factor:	>0.95
Emer 3 hour as above	/EM3	Luminaire efficacy:	Up to 119lm/w
		Control:	DALI driver available
		Weight:	2.7kg
		Ambient temp:	-20°C to 25°C
Standard options	Order code		
3000K 27W 2689lm	1833127		
4000K 26W 3081lm	1843127		
3000K 36W 3585lm	1833136		
4000K 35W 3900lm	1843135		