




Description

Linnet/IK10 IP65 LED Moisture proof luminaire is available for surface or suspended installations. Linnet/IK10 is made from robust injection moulded polycarbonate body with micro prism, high impact diffuser. The Tridonic LEDs strips are covered with a micro prismatic diffuser for visual comfort and efficiency. High system efficacy to aid compliance with Building Regulations Part L and quick release flush mounted stainless steel fixing clips.

Linnet/IK10 are ideal for installations with low ambient temperatures ideal for undercover car parks as well as warehouse, back of house and food areas, to name a few.

Dimming, sensor and emergency are all an option along with other options as below. It is an ideal replacement for fluorescent luminaires and can offer great savings and a fast pay back. Please email for more details or if survey required

Wall Bracket



Options

Description

DALI Dimmable
Emer 3 hour integral
Sensor on/off
Stainless steel clips
Wall bracket
Sus kit 1.5m
PIR Sensor

Add to part code

/DALI
/EM3
/SO
/SS
/WB
/SK1.5
/PIR

Standard options

3675lm 23W 4000K 1200mm
4475lm 28.5W 4000K 1200mm
5325lm 35.5W 4000K 1200mm
6100lm 40.5W 4000K 1200mm

Order code

3846123-1200-IK10
3846128-1200-IK10
3846135-1200-IK10
3846140-1200-IK10

5300lm 33W 4000K 1500mm
6625lm 41.5W 4000K 1500mm
7950lm 50W 4000K 1500mm
9250lm 59W 4000K 1500mm

3846133-1500-IK10
3846141-1500-IK10
3846150-1500-IK10
3846159-1500-IK10

Information

Light Source:	LED
Wattage:	Various see options
Housing	Polycarbonate
Diffuser	Micro Prismatic
IP rating:	IP65
Impact protection:	IK10
Power Factor:	>0.9
MacAdam:	3SDCM
Colour rendering:	Ra80
Lifetime:	50,000 hours+
Maximum Weight:	3kg & 4kg
Ambient temp:	-25°C to 35°C